

Diotrol Entgrauer

Degreying agent

#82500

Description Diotrol Degreying agent turns wood back into its natural look and restores all kinds of greyed wood. It refreshes wood that was exposed to UV radiation and weathering. Diotrol Degreying agent refreshes greyed shutter, planking and massive furniture.

Application area greyed wood (shutters, wood siding, garden furniture)

Binder / reactive agents Hydrous solution of organic acids, completely biodegradable.

Active agents / Biocide none

Spec. Gravity App. 1.000 kg/l

Tints Colourless

Packaging 1L, 2L, 5L

Storage 12 months in appropriate cool place, and in closed original packaging. Close packaging properly after usage. Prevent from freezing, and temperature of more than 30°C.

Surface Remove moss, lichen as well as dried breakout of natural resin before mechanically use. Highly soiled parts of the building must be previously cleaned with Diolin Allclean.

Processing Brush, roller, nylon brush,
Do not use below + 5 ° C or above + 30 ° C.

Consumption 5 – 8m² per liter Diotrol Degreying agent. The consumption varies, depending on the kind of wood and its surface structure.

Dilution ready to use

Paint system Agitate well before use. Do not dilute. The jellylike product is ready to use.

- Moisture wood prior to use to optimise the effect.
- Apply saturating with brush or roll (long haired).
- Vertical parts are treated top down.
- Allow to act 10 to max. 15 minutes. If needed, finish with a nylon brush (caution acid spilling!)
- Rins area with plenty of water. Reduce pressure of high-pressure cleaner to prevent grain raising.
- Possibly repeat cleaning procedure on strongly soiled surfaces.
- Let dry well.

Before use, make a cleaning test on a non-visible place. Diotrol Degreying agent should not dry.

In case of doubt or uncertainties, please contact the technical service.

Drying at 18 – 20°C (at 50% rel. moisture)

Let dry for a minimum of 2 – 3 days. The drying is depending on weathering and varies according to water uptake and property of wood.

Cleaning of tools

Clean immediately with water.

Safety advice

Please read safety data sheet.

Wearing rubber gloves, eye protection and protective clothing is recommended. Do not bring into contact with crops.

Remarks

This information is due to the current, technical know-how and are meant as recommendation and advice. Concerning all mentioned paint coat structures we do not maintain completeness. Insufficient wood quality, lack of constructive wood-protection, drying cracks in solid wood and otherwise identified faults have to be admonished by the customer before painting or glazing. Because of the diversification and different kinds of substrates and practice, the user has to test our products mainly for his own purpose and has to use and apply them properly. For this, he is fully responsible. Verbal advice must be fixed obligatory by a signed document. If a new issue will be current, this edition will be no more available

September 2018 mt/ms