## according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

3-Pigments white

 Print date:
 02.05.2017
 Revision date: 17.03.2017
 EN

 Version:
 8.19
 Issue date: 17.03.2017
 Page 1 / 7

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. product identifiers

Article No. (manufacturer/supplier) 260

Identification of the substance or mixture 3-Pigments white

LH-260

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Paint to protect surfaces

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

Knuchel Farben AG

Farben + Lacke Telephone: +41 (0) 32 636 50 40 Steinackerweg 11 Telefax: +41 (0) 32 636 50 45

CH-4537 Wiedlisbach

Dept. responsible for information:

laboratory Manager

E-mail (competent person) info@knuchel.ch

1.4. Emergency telephone number

Emergency telephone number 145 (+41 (0)44 251 51 51)

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226 Flammable liquids Flammable liquid and vapour.

2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

## **Hazard pictograms**



#### Warning

#### **Hazard statements**

H226 Flammable liquid and vapour.

## **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of the reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take precautionary measures against static discharges.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to industrial incineration plant.

contains:

not applicable

## Supplemental Hazard information (EU)

EUH208 Contains 2-butanone oxime. May produce an allergic reaction.

#### 2.3. Other hazards

## **SECTION 3: Composition / information on ingredients**

## 3.2. Mixtures

## Product description / chemical characterization

**Description** solvent-based alkyd resin, containing the following hazardous substances:

Hazardous ingredients

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

3-Pigments white

Print date: 02.05.2017 Revision date: 17.03.2017 EN Version: 8.19 Revision date: 17.03.2017 Page 2 / 7

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Chemical name classification // Remark	Wt %
919-857-5 64742-48-9 649-327-00-6	01-2119463258-33 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics Flam. Liq. 3 H226 / Asp. Tox. 1 H304	20 - 25
918-481-9 64742-48-9 649-327-00-6	01-2119457273-39 Kohlenwasserstoffe, C11-C14, < 2 % Aromaten n-Alkane, iso-Alkane, cyclische Verbindungen Asp. Tox. 1 H304	2,5 - 5
202-496-6 96-29-7 616-014-00-0	01-2119539477-28 2-butanone oxime Carc. 2 H351 / Acute Tox. 4 H312 / Eye Dam. 1 H318 / Skin Sens. 1 H317	0,5 - 1
219-535-8 2457-01-4		
245-018-1 22464-99-9	Fatty acid C6-C19, zirconium Repr. 2 H361	< 0,5

#### **Additional information**

Full text of classification: see section 16

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

## Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

## After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

## After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

## 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

## 4.3. Indication of any immediate medical attention and special treatment needed

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

## Extinguishing media which must not be used for safety reasons:

strong water jet

#### 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

## 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do

## according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

3-Pigments white

Print date: 02.05.2017 Revision date: 17.03.2017 EN Version: 8.19 Issue date: 17.03.2017 Page 3 / 7

not allow water used to extinguish fire to enter drains, ground or waterways.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

## 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

#### 6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

#### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### Occupational exposure limit values:

not applicable

## 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

### Occupational exposure controls

## Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection

## according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

3-Pigments white

 Print date:
 02.05.2017
 Revision date: 17.03.2017
 EN

 Version:
 8.19
 Issue date: 17.03.2017
 Page 4 / 7

apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

## **Hand protection**

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Eye protection

Wear closely fitting protective glasses in case of splashes.

#### **Protective clothing**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

#### Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Appearance:

Physical state: liquid
Colour: refer to label
Odour: characteristic
Odour threshold: not applicable
pH at 20 °C: not applicable
Melting point/freezing point: not applicable

Initial boiling point and boiling range: 150 °C

Source: Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds,

<2% aromatics

Flash point: 40 °C

Evaporation rate: not applicable

Flammability (solid, gas):

burning time (s): not applicable

Upper/lower flammability or explosive limits:

Lower explosion limit: 0,8 Vol-% Upper explosion limit: 7 Vol-%

Source: Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds,

<2% aromatics

Vapour pressure at 20 °C: 5 mbar

Source: Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds,

<2% aromatics

Vapour density: not applicable

Relative density:

Density at 20 °C: 1,36 g/cm<sup>3</sup>

Solubility(ies):

Water solubility (g/L) at 20 °C: insoluble
Partition coefficient: n-octanol/water: see section 12

Auto-ignition temperature: 240 °C

Source: Kohlenwasserstoffe, C11-C14, < 2 % Aromaten n-Alkane,

iso-Alkane, cyclische Verbindungen

Decomposition temperature: not applicable Viscosity at 20 °C: 80 s 4 mm

Method: DIN 53211

## according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

3-Pigments white

02.05.2017 Revision date: 17.03.2017 Print date: Page 5 / 7 Version: Issue date: 17.03.2017

**Explosive properties:** not applicable Oxidising properties: not applicable

Other information 9.2.

> Solid content (%): 71 Wt %

solvent content:

Organic solvents: 29 Wt % Water: 0 Wt %

Solvent separation test (%): < 3 Wt % (ADR/RID)

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

#### 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

#### 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

#### 10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

#### **SECTION 11: Toxicological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

No data on preparation itself available.

#### 11.1. Information on toxicological effects

#### **Acute toxicity**

Toxicological data are not available.

## skin corrosion/irritation; Serious eye damage/eye irritation

Toxicological data are not available.

#### Respiratory or skin sensitisation

Toxicological data are not available.

#### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Toxicological data are not available.

## Specific target organ toxicity

Toxicological data are not available.

## **Aspiration hazard**

Toxicological data are not available.

## Practical experience/human evidence

## Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

## **Overall Assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

#### **SECTION 12: Ecological information**

## overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP]

## according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

3-Pigments white

Print date: 02.05.2017 Revision date: 17.03.2017 EN Version: 8.19 Issue date: 17.03.2017 Page 6 / 7

There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

#### 12.1. **Toxicity**

Toxicological data are not available.

#### 12.2. Persistence and degradability

Toxicological data are not available.

#### 12.3. Bioaccumulative potential

Toxicological data are not available.

#### 12.4. Mobility in soil

Toxicological data are not available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

## Appropriate disposal / Product

#### Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

## List of proposed waste codes/waste designations in accordance with EWC

080111 waste paint and varnish containing organic solvents or

other dangerous substances

#### packaging

#### Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

#### **SECTION 14: Transport information**

## 14.1. UN number

UN 1263

#### 14.2. UN proper shipping name

Land transport (ADR/RID): Paint
Sea transport (IMDG): PAINT
Air transport (ICAO-TI / IATA-DGR): Paint

14.3. Transport hazard class(es)

Land transport (ADR/RID): KEINE GÜTER DER KLASSE 3

bei Gebinden > 450 I Klasse 3

Sea transport (IMDG) 3

for packages < 30 litres: Transport in accordance with the provisi ons of paragraph 2.3.2.5 of the

IMDG Cod e.

Air transport (ICAO-TI / IATA-DGR) 3

14.4. Packing group

Ш

14.5. Environmental hazards

Land transport (ADR/RID) not applicable
Marine pollutant not applicable

#### 14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

#### **Further information**

#### Land transport (ADR/RID)

tunnel restriction code D/E

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830

3-Pigments white

Print date: 02.05.2017 Revision date: 17.03.2017 EN Version: 8.19 Issue date: 17.03.2017 Page 7 / 7

#### Sea transport (IMDG)

EmS-No. F-E, S-E

Air transport (ICAO-TI / IATA-DGR)

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** legislation

#### Directive 2010/75/EU on industrial emissions

VOC-value (in g/L): 397

#### **National regulations**

#### **Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

### 15.2. Chemical Safety Assessment

#### For the following substances of this preparation a chemical safety assessment has been carried out:

EC No.	Chemical name					REACH No.		
CAS No.								
918-481-9	Kohlenwasserstoffe,	C11-C14,	<	2	%	Aromaten	n-Alkane,	01-2119457273-39
64742-48-9	iso-Alkane, cyclische	iso-Alkane, cyclische Verbindungen						

#### **SECTION 16: Other information**

## Full text of classification in section 3:

Flammable liquids	Flammable liquid and vapour.
Aspiration hazard	May be fatal if swallowed and enters airways.
Carcinogenicity	Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Acute toxicity (dermal)	Harmful in contact with skin.
Serious eye damage/eye irritation	Causes serious eye damage.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Acute toxicity (oral)	Harmful if swallowed.
Reproductive toxicity	Suspected of damaging the unborn child.
Reproductive toxicity	Suspected of damaging fertility. Suspected of damaging the unborn child.
	Aspiration hazard Carcinogenicity  Acute toxicity (dermal) Serious eye damage/eye irritation Respiratory or skin sensitisation Acute toxicity (oral) Reproductive toxicity

#### Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

#### **Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.